







Reliable process monitoring | Simple integration

Typical Applications: Wastewater | Source Water | Swimming Pool & Spa

	TRANSMITTERS			CONTROLLERS	
	TX10	TX100	TX20	TX3000	TX2000 (RS)
					
<b>RANGE</b>	-2.00...+16.00pH -1999mV...+1999mV	0.00...14.00pH -1999mV...+1999mV	-2.00...+16.00pH -1999mV...+1999mV	-2.00...+16.00pH -1999mV...+1999mV	-2.00...+16.00pH -1999mV...+1999mV
<b>TEMPERATURE</b>	ATC -10...+120°C	ATC -20...+110°C	ATC -10...+120°C	ATC -30...+130°C	ATC -30...+130°C
<b>RESOLUTION</b>	0.01pH 1mV	0.01pH 1mV	0.01pH 1mV	0.01pH 1mV	0.01pH 1mV
<b>4-20mA OUTPUTS</b>	<b>1</b>	<b>1</b>		<b>2</b>	<b>2 (1)</b>
<b>MODBUS OUTPUTS</b>					<b>0 (1)</b>
<b>ALARM/CONTROL RELAYS</b>			✓	✓	✓
<b>WATER RESISTANT</b>		✓		✓	✓
<b>PANEL MOUNT</b>	✓	✓	✓	✓	✓
<b>WALL MOUNT</b>		✓		✓	✓
<b>GRAPHICAL DISPLAY</b>					✓
<b>DIMENSIONS</b>	1/8 DIN: 3.78" (96 mm) x 1.89" (48 mm)	1/4 DIN: 3.9" (99 mm) x 3.9" (99 mm)	1/8 DIN: 3.78" (96 mm) x 1.89" (48 mm)	1/2 DIN: 5.7" (145 mm) x 5.7" (145 mm)	1/4 DIN: 3.78" (96 mm) x 3.78" (96 mm)
<b>DEPTH</b>	3.54" (90 mm)	2.9" (74 mm)	3.54" (90 mm)	5.20" (132 mm)	4.5" (114 mm)
<b>POWER</b>	100-240 VAC 50/60 Hz	12-24 VDC (Loop)	100-240 VAC 50/60 Hz	100-240 VAC 50/60 Hz	100-240 VAC 50/60 Hz